

GB Induction Lighting Ltd

53 London Road
Camberley
Surrey, GU15 3UG

☎: +44 (0) 1276 490 381
✉: info@gbinductionlighting.co.uk
🌐: www.gbinductionlighting.co.uk



Induction Lighting

Specifications: High Bay

F002

- Available in 80W, 120W, 200W, 300W
- Fixture is made from die cast aluminium
- Lampshade is made from polycarbonate material
- Is resistant to high temperatures, has a high transmittance and is glare proof
- Used in large spaces such as supermarkets, auditoriums, factories and warehouses

Technical Data

Rated voltage	220V
Shell protection	IP54
Insulation grade	I
Anticorrosion grade	WF2
Installation height	8 - 15m
Wattage	80 – 300W

Electrical Parameters

Input Voltage	97 – 277V AC
Power Frequency	47 – 63Hz
Output Frequency	250KHz
Total Power Consumption	86 – 323W
Power Efficiency	92%
Power Factor	≥ 0.95

Optical Parameters

200w Circular Lamp and Ballast	
Colour Temperature	2700 – 6500K
Fixture Efficiency	79%
Light Efficiency	82.5lm/W
Luminous Flux	6500 - 24500lm
Colour Rendering Index	≥ 75 - 82

Other Parameters

Operating Temperature Range	-40 through to +50 centigrade
Average Lifespan	100 000 hrs
Lumen Maintenance	80 000 hrs – 80%
HID Replacement	150W – 600W
Net Weight	6.9 kgs
Fixture Dimensions	550 x 550 x 400mm
Carton Dimensions	570 x 570 x 450mm

