

GB Induction Lighting Ltd

53 London Road
Camberley
Surrey, GU15 3UG

☎: +44 (0) 1276 490 381
✉: info@gbinductionlighting.co.uk
🌐: www.gbinductionlighting.co.uk



Induction Lighting

Specifications: Flood Light

FD001

- Available in 150W, 200W, 250W
- Fixture made from die cast aluminium
- Reflector made of high quality polished anodised aluminium
- Front lens toughened flat glass with heat resistant silicon rubber sealing ring
- Front cover lifts for easy maintenance

Technical Data

Rated voltage	220V
Shell protection	IP65
Insulation grade	I
Anticorrosion grade	WF2
Installation height	6 - 8m
Wattage	150 – 250W

Electrical Parameters

Input Voltage	97 – 277V AC
Power Frequency	47 – 63Hz
Output Frequency	250KHz
Total Power Consumption	161 - 269W
Power Efficiency	≥ 94%
Power Factor	≥ 0.95

Optical Parameters

200 W Rectangular Lamp and Ballast	
Colour Temperature	2700 – 6500K
Fixture Efficiency	≥ 62%
Light Efficiency	≥ 84 lm/W
Luminous Flux	1200 - 20500lm
Colour Rendering Index	≥ 82

Other Parameters

Operating Temperature Range	-40 through to +50 centigrade
Average Lifespan	100 000 hrs
Lumen Maintenance	80 000 hrs – 80%
HID Replacement	300 - 500W
Net Weight	13.9 kgs
Fixture Dimensions	530 x 530 x 300mm
Carton Dimensions	590 x 590 x 320mm

