

# GB Induction Lighting Ltd

53 London Road  
Camberley  
Surrey, GU15 3UG

☎: +44 (0) 1276 490 381  
✉: info@gbinductionlighting.co.uk  
🌐: www.gbinductionlighting.co.uk



Induction Lighting

## Specifications: Wall Light

W001

- Rectangular – Available in 40W and 60W
- High aluminium casting body
- High borax glass lens
- Used at warehouses, indoor parking, offices, factories and passageways

### Technical Data

Rated voltage	220V
Shell protection	IP65
Insulation grade	I
Anticorrosion grade	WF2
Installation height	3 - 6m
Wattage	40 – 60W



### Electrical Parameters

Input Voltage	97 – 277V AC
Power Frequency	47 – 63Hz
Output Frequency	250KHz
Total Power Consumption	44 – 66W
Power Efficiency	≥ 94%
Power Factor	≥ 0.95

### Optical Parameters

40 - 60 W Rectangular Lamp and Ballast	
Colour Temperature	2700 – 6500K
Fixture Efficiency	≥ 85%
Light Efficiency	≥ 84 lm/W
Luminous Flux	3400 - 5100lm
Colour Rendering Index	≥ 82

### Other Parameters

Operating Temperature Range	-40 through to +50 centigrade
Average Lifespan	100 000 hrs
Lumen Maintenance	80 000 hrs – 80%
HID Replacement	80 - 120W
Net Weight	3.45kgs
Fixture Dimensions	370 x 230 x 190mm
Carton Dimensions	390 x 255 x 220mm

